## Site Qualification Form

## Wired Ethernet Connectivity for CP6000

Due to the complexity of installation, this form must be completed prior to the sale of any Ethernet kit for CP6000.

## **General information**

Customer Information	
Customer name	
Customer contact name	
Customer contact phone	
Customer contact email	
Street	
City	
County/Region	
Country	
Postcode	



Is a LAN already on site that has an available	Yes
Ethernet port in the switch/router?	Notes I ANI patricipals in proportional levels a gita least
	<b>Note:</b> LAN network is managed by the site host. ChargePoint is only responsible for providing an Ethernet port on the charging station.
Is the LAN configured in DHCP or Static IP mode?	DHCP
	Static IP
	<b>Note:</b> ChargePoint recommends DHCP mode. If specific IP addresses are required, ChargePoint recommends utilising DHCP Reservation on the network device. If Static IP is selected, please provide the specific IP address.
Does the LAN utilise IPv4?	Yes
	<b>Note:</b> ChargePoint requires the use of IPv4 at this time.
Is the LAN a shared network?	Yes
	No
	<b>Note:</b> ChargePoint recommends an isolated network with device isolation.
If the LAN has an outbound firewall, are connections enabled on the following ports:	Yes
Usage: HTTPS, Protocol: TCP, Port: 443     Usage: HTTPS, Protocol: TCP, Ports: 52007	
<ul> <li>Usage: VPN, Protocol: TCP, Ports: 52007 - 52017</li> </ul>	
Usage: NTP, Protocol: UDP, Port: 123	
Has the site connectivity been validated?	Yes
1. Is an IP assigned (Link State)?	
2. Is the VPN server reachable from the network (VPN)?	
Refer to the <i>Network Configuration for Ethernet</i> and <i>VPN connectivity</i> on CP6000 for more details.	
Does the ethernet cable meet the required specification for the length of run?  Less than 100m:	Yes
An outdoor rated Cat6 Shield Twisted	

Pair (STP) cable or above must be used (i.e. Cat 6a, 7, Cat 7a, Cat 8).	
Between 100m and 200m:	
An Page OSP Shielded GameChanger must be used. No other ethernet cable is qualified for this application.  Note: Ethernet runs cannot be longer than 200m.	
Is the cable shield grounded?	Yes
Is a ferrite cable core, model Wurth 742 758 15, placed inside the charger on the LAN cable (Provided with the USB to Ethernet Kit)?	Yes

ļ,	confirm that all information provided by me
in this form is accurate.	

Signature	Title	Date

## Legal disclaimer

ChargePoint is not responsible for verifying this information, and the creator of the protocol remains responsible for this information.

ChargePoint accepts no ongoing responsibilities for the electrical design and the installation specifics.



chargepoint.com/support