

ChargePoint® Express Distro Power Block 2000

One platform, infinite possibilities



Express Distro Power Block 2000 Specifications

Electrical

Input Voltage Rating	3-phase, 400Y VAC, 50 Hz		
Max Output Power, Single Cabinet, 400 VAC	350 kW Paired: 500 kW	500 kW	525 kW Paired: 625 kW, 750 kW
Input Current Rating, AC	542 A	789 A	809 A
Max Output Power, Double Cabinet	1.05 MW		
Max Output Power, Triple Cabinet	1.58 MW		
Wiring	L1, L2, L3, Earth. N available for V2G functionality		
Short Circuit Current Rating	100 kA		
Output Voltage, Charging	100 to 1000 VDC		
Max Current per DC output*	800 A, 1000 A peak		
DC Outputs per cabinet	4, 8, 12		
Power Conversion Efficiency	Up to 97%		
Power Factor	0.99 at full load		
Harmonics	iTHD < 5% (Complies with IEEE 519)		
Standby Power, Single Cabinet	60W		
Bidirectional Energy Flow	Hardware ready		
Power Allocation Increments	43 ~ 62.5 kW Paired: 50 ~ 62.5 kW		

Connectivity

Service and Maintenance	Remote system monitoring, diagnostic, and proactive maintenance
-------------------------	---

ChargePoint, Inc. reserves the right to alter product offerings and specifications at any time without notice, and is not responsible for typographical or graphical errors that may appear in this document.

Software Updates	Firmware updated over-the-air (OTA)
------------------	-------------------------------------

Safety Ratings

Safety and Compliance	Testing in progress CE and UKCA marked. Complies with IEC 61851-1 and IEC 61851-23 RoHS
Station Surge Protection	Tested to IEC 6100-4-5, Level 5 (6 kV @ 3,000 A)
EMC Compliance	EN55011, EN55022, and IEC 61851-21-2 Class A

Generic Specifications

Indicators	Status LEDs for diagnostics
Enclosure Dimensions (W x D x H)	Single: 995 x 778 x 2350 mm, 39.2 x 30.7 x 92.6 in Double: 1990 x 778 x 2350 mm, 78.4 x 30.7 x 92.6 in Triple: 2985 x 778 x 2350 mm, 117.6 x 30.7 x 92.6 in
Enclosure Rating	Type 3R, IP55
Impact Rating	IK10
Mounting Type	Ground
Weight, Single Cabinet	1300 kg (2840 lb) with all modules installed
Storage Temperature	-40°C to 70°C (-40°F to 158°F)
Operating Temperature	-40°C to 55°C (-40°F to 131°F) with derating
Operational Altitude	3,000 m (9,800 ft) without derating, 4000 m (13,123 ft) with derating
Operating Humidity	Up to 95% at 50°C (122°F) non-condensing
Standard Warranty	Limited 2-Year Parts and Labor Warranty

Energy Management Features

Dynamic Power Management	Allows a fixed maximum power output per station or lets the system dynamically manage the power distribution per station
--------------------------	--

Contact Us

ChargePoint, Inc.
240 East Hacienda Avenue
Campbell, CA 95008-6617 USA

+1.408.841.4500 or
+1.877.370.3802 US and Canada toll-free

Visit chargepoint.com
Call +1.408.705.1992
Email sales@chargepoint.com

Copyright © 2025 ChargePoint, Inc. All rights reserved. CHARGEPOINT is a U.S. registered trademark/service mark, and an EU registered logo mark of ChargePoint, Inc. All other products or services mentioned are the trademarks, service marks, registered trademarks or registered service marks of their respective owners. Apr 2026



ChargePoint, Inc. reserves the right to alter product offerings and specifications at any time without notice, and is not responsible for typographical or graphical errors that may appear in this document.