

ChargePoint® Express Distro Power Block 2000

One platform, infinite possibilities



Express Distro Power Block 2000 Specifications

Electrical

Input Voltage Rating	3-phase, 480Y VAC, 60 Hz 3-phase, 600Y VAC, 60 Hz		
Max Output Power, Single Cabinet, 480 VAC	200 kW	400 kW Paired: 500 kW	600 kW Paired: 625 kW, 750 kW
Max Output Power, Single Cabinet, 600 VAC	225 kW	450 kW	625 kW
Input Current Rating, AC	480 V: 258 A 600 V: 232 A	480 V: 515 A 600 V: 463 A	480 V: 769 A 600 V: 641 A
Max Output Power, Double Cabinet	480 VAC: 1.20 MW 600 VAC: 1.35 MW		
Max Output Power, Triple Cabinet	480 VAC: 1.80 MW 600 VAC: 1.88 MW		
Wiring	L1, L2, L3, Earth		
Short Circuit Current Rating	100 kA		
Output Voltage, Charging	100 to 1000 VDC		
Max Current per Output	200 ~ 225 kW: 500 A 400 ~ 600 kW: 800 A, 1000 A peak		
Outputs per Cabinet	4, 8 and 12 optional		
Power Conversion Efficiency	Up to 97%		
Power Factor	0.99 at full load		
Harmonics	iTHD < 5% (Complies with IEEE 519)		
Standby Power, Single Cabinet	60W		
Bidirectional Energy Flow	Hardware ready		
Power Allocation Increments	50 ~ 62.5 kW		

ChargePoint, Inc. reserves the right to alter product offerings and specifications at any time without notice, and is not responsible for typographical or graphical errors that may appear in this document.

Connectivity

Service and Maintenance	Remote system monitoring, diagnostic, and proactive maintenance
Software Updates	Firmware updated over-the-air (OTA)

Safety Ratings

Safety and Compliance	Testing in progress cUL and UL listed. Complies with UL 2202, UL1741 Energy Star RoHS
Station Surge Protection	Tested to IEC 6100-4-5, Level 5 (6 kV @ 3,000 A)
EMC Compliance	FCC part 15 Subpart B Class A

Generic Specifications

Indicators	Status LEDs for diagnostics
Enclosure Dimensions (W x D x H)	Single: 995 x 778 x 2336 mm, 39.2 x 30.7 x 92.0 in Double: 1990 x 778 x 2336 mm, 78.4 x 30.7 x 92.0 in Triple: 2985 x 778 x 2336 mm, 117.6 x 30.7 x 92.0 in
Enclosure Rating	Type 3R, IP55
Impact Rating	IK10
Mounting Type	Ground
Weight, Single Cabinet	Up to 1300 kg (2840 lb) with all modules installed
Storage Temperature	-40°C to 70°C (-40°F to 158°F)
Operating Temperature	-40°C to 55°C (-40°F to 131°F) with derating
Operational Altitude	3,000 m (9,800 ft) without derating, 4000 m (13,123 ft) with derating
Operating Humidity	Up to 95% at 50°C (122°F) non-condensing
Buy America	FTA, FHWA, BABA available upon request

ChargePoint, Inc. reserves the right to alter product offerings and specifications at any time without notice, and is not responsible for typographical or graphical errors that may appear in this document.

Standard Warranty	Limited 2-Year Parts Warranty
-------------------	-------------------------------

Energy Management Features

Dynamic Power Management	Allows a fixed maximum power output per station or lets the system dynamically manage the power distribution per station
--------------------------	--

Contact Us

ChargePoint, Inc.
 240 East Hacienda Avenue
 Campbell, CA 95008-6617 USA
 +1.408.841.4500 or
 +1.877.370.3802 US and Canada toll-free

Visit chargepoint.com
 Call +1.408.705.1992
 Email sales@chargepoint.com

Copyright © 2025 ChargePoint, Inc. All rights reserved. CHARGEPOINT is a U.S. registered trademark/service mark, and an EU registered logo mark of ChargePoint, Inc. All other products or services mentioned are the trademarks, service marks, registered trademarks or registered service marks of their respective owners. Apr 2026



ChargePoint, Inc. reserves the right to alter product offerings and specifications at any time without notice, and is not responsible for typographical or graphical errors that may appear in this document.